

## Europäisches Patentamt

**European Patent Office** 

Office européen des brevets



EP 1 209 651 A2

(12)

# **EUROPEAN PATENT APPLICATION**

(43) Date of publication:

29.05.2002 Bulletin 2002/22

(51) Int Cl.7: G09G 3/20

(11)

(21) Application number: 01307922.3

(22) Date of filing: 18.09.2001

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU

MC NL PT SE TR

**Designated Extension States:** 

AL LT LV MK RO SI

(30) Priority: 21.11.2000 US 717784

(71) Applicant: Nokia Corporation

02150 Espoo (FI)

(72) Inventor: Heiskari, Heli 20100 Turku (FI)


(74) Representative: Read, Matthew Charles et al Venner Shipley & Co.

20 Little Britain

London EC1A 7DH (GB)

#### (54)Three-dimensional icons for graphical user interface

A strong three-dimensional icon is created for low-resolution displays such as used in portable communication devices by alternating light and dark stripes, with some stripes changing from light to dark and back to light to indicate a shadow, and other stripes from dark to light and back to dark to indicate a highlight. Altogether, the light and dark stripes with shadows and highlights provide the icon with a strong three-dimensional appearance.



Printed by Jouve, 75001 PARIS (FR)

## Description

## BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

[0001] The invention relates to user interface graphics for mobile phones or other portable electronic devices with displays.

## 2. Description of the Related Art

[0002] For low-resolution displays of portable communication devices, images presented thereon have in the past had strong two-dimensional characteristics. It would be advantageous to add value to the display of images for such devices to give a more three-dimensional effect and thereby increase the impact of the imagery presented.

### BRIEF SUMMARY OF THE INVENTION

[0003] An object of the present invention is to make possible the presentation of low-resolution images with strong three-dimensional effect.

[0004] According to a first aspect of the invention, a computer-readable medium encoded with a data structure for use in providing a graphical icon for display on a display of a portable communications device is characterized in that said data structure is encoded as digital data indicative of said graphical icon defined by alternating light and dark stripes, that selected stripes of said light and dark stripes change from light to dark and back to light to indicate a shadow adjacent an edge of said icon and from dark to light and back to dark to indicate a highlight adjacent another edge of said icon, and that altogether said light and dark stripes with shadows and highlights provide said icon with a three-dimensional appearance.

[0005] According to a second aspect of the invention, a communication device comprises means responsive to an event in the communication device for providing an event signal, a computer readable medium encoded with a data structure for use in providing a graphical icon for display on a display of a portable communications device, wherein the data structure is encoded as digital data indicative of said graphical icon defined by alternating light and dark stripes, wherein selected stripes of said light stripes change from light to dark and back to light to indicate a shadow adjacent an edge of said icon and from dark to light and back to dark to indicate a highlight adjacent another edge of said icon, and that altogether said light and dark stripes with shadows and highlights provide said icon with a three-dimensional appearance, and means responsive to the event signal for retrieving the digital data from the computer-readable medium and causing said display of said graphical icon on said display according to said retrieved digital data.

[0006] According to a third aspect of the invention, a method of displaying an icon on a portable communication device comprises the steps of retrieving, in response to an event signal, digital data from a computer-readable medium, and displaying said icon in response to said digital data retrieved from said computer-readable medium, wherein said digital data is indicative of said icon defined by alternating light and dark stripes, that selected stripes of said light and dart stripes change from light to dark and back to light to indicate a shadow adjacent an edge of said icon and from dark to light and back to dark to indicate a highlight adjacent another edge of said icon, and that altogether said light and dark stripes with shadows and highlights provide said icon

[0007] Further according to the first, second and third aspects of the invention, said digital data is encoded according to a portable bitmap file format.

with a three-dimensional appearance.

[0008] Still further according to the first, second and third aspects of the invention, said digital data is encoded according to a portable graymap file format.

[0009] Further still according to the first, second and third aspects of the invention, said digital data is encoded according to a portable color image file format.

25 [0010] These and other objects, features and advantages of the present invention will become more apparent in light of the detailed description of a best mode embodiment thereof, as illustrated in the accompanying drawing.

## BRIEF DESCRIPTION OF THE DRAWING

## [0011]

30

35

Fig. 1 shows a mobile communication device, according to the present invention, with a graphical icon defined by alternating light and dark stripes.

Fig. 2A shows an "outdoor" graphical icon, according to the present invention.

Fig. 2B shows a "meeting" graphical icon, according to the present invention.

Fig. 2C shows a "silent" graphical icon, according to the present invention.

Fig. 2D shows a "footprint" graphical icon, according to the present invention.

Fig. 2E shows a "butterfly" graphical icon, according to the present invention.

Fig. 2F shows an enlarged view of Fig. 2E to better illustrate the alternating light and dark stripes, according to the present invention.

Fig. 3 shows a portable communication device, according to the present device.

Fig. 4 shows a series of steps which may be carried out in the device of Fig. 3, according to the present invention.

20

25

## **DETAILED DESCRIPTION OF THE INVENTION**

[0012] Fig. 1 shows a communication device 10 in the form of a mobile station or wireless user terminal such as, but not limited to, a cellular radio telephone or personal communicator that is suitable for displaying an image 12, according to the present invention. The image 12 is defined by alternating light and dark stripes, as shown. Selected stripes change from light to dark and back to light to indicate a shadow adjacent to an edge of a feature of the icon. Stripes also change from dark to light and back to dark to indicate a highlight adjacent another edge of a feature of the icon. Altogether, the light and dark stripes with shadows and highlights provide the icon with a three-dimensional appearance, much like a bas-relief.

[0013] The communication device 10 of Fig. 1 includes a display 14, a keypad 16, a microphone 18 and a speaker 20. An antenna is located behind the speaker at the back of the device 10 and is not shown in Fig. 1. The keypad 16 may be covered by a sliding cover 22 when the keypad is not in use.

[0014] It is noted from the icon 12 of Fig. 1 that the image there shown is of a graph, for instance of a stock price over time and has a strong three-dimensional effect on the viewer which makes the image of the graph stand out more than it otherwise would if it had been rendered as a simple two-dimensional graph, as has been the case in the prior art.

[0015] Some examples of such images will now be shown. For instance, Fig. 2A shows a scene of a city which can be used as an icon to symbolize an "outdoor" context for an application of the device 10. As can be seen, it is made up of vertical stripes that alternate between light and dark. Selected stripes are interrupted and change from dark to light or vice versa and may change back again, although not necessarily. These changes from light to dark in a given stripe permit the designer to create effects of highlighting and shadowing on the displayed objects in order to suggest the presence of an imaginary light source casting light from a given direction toward the objects. In Fig. 2A, the imaginary light source is coming from the upper left and therefore the highlighting occurs on the left-hand side of the buildings illustrated, while shadowing occurs on the right-hand side.

[0016] Similarly, Fig. 2B shows a "meetings" icon which is also made up of vertical stripes alternating between light and dark. Again, an imaginary light source to the upper left creates highlighting to the left and top of the illustrated briefcase, while shadowing occurs at the bottom and right-hand side thereof. A given vertical stripe may change from dark to light or light to dark and back again, or stay the same.

[0017] Fig. 2C shows a "silent" in the form of a water lily with an imaginary light source coming from directly above. The outstretched leaves of the lily are highlighted at the top edges thereof and are shadowed underneath.

Each "leaf can be thought of as a feature of an iconic representation of a water lily, which is made of alternating light and dark vertical stripes, according to the present invention.

[0018] Fig. 2D shows a "footprint" icon with alternating light and dark vertical stripes, according to the present invention. A given light or dark stripe can change from dark to light or light to dark and remain that way or change back to the original shade. The footprint is shown Illuminated from directly above by an imaginary light source, the same way as in Fig. 2C, with shadowing underneath.

[0019] Fig. 2E shows a "butterfly" icon, again illuminated from above, and made up of alternating light and dark vertical stripes, according to the present invention. Fig. 2F shows an enlargement of Fig. 2E in order to better appreciate the changing of the vertical stripes. For instance, a first dark stripe 24 at the left edge stays dark throughout the full extent thereof. The same can be said for the second stripe, which is a light-shaded stripe that does not change throughout its extent. A third stripe which is dark shaded also does not change and remains dark throughout. A fourth stripe 30 is light colored for most of its extent, but includes a short dark portion near the top and which indicates a shadow adjacent an edge of the icon of the butterfly, i.e., a shadow under the tip of its left wing. The light-shaded vertical stripe 30 starts out as light shaded and then changes to dark shaded and changes back again to light shaded. A next stripe 32 is dark shaded for most of its extent, but has a short part near the top that is used to indicate a highlight at the top tip of the left wing of the butterfly icon. This is an instance of a dark-shaded stripe changing from dark to light and back to dark again to indicate a highlight adjacent another edge of the icon of the butterfly. Altogether, these alternating light and dark stripes with parts indicating shadows and highlights provide the icon with a strong three-dimensional appearance.

[0020] All of these icons resemble scupltural reliefs in which the projection from the surrounding surface is slight and no part of the modeled form is undercut.

[0021] Fig. 3 shows the communication device of Fig. 1 as schematic block diagram. The previously-mentioned display, keypad, microphone and speaker are shown to the right of Fig. 3. They are connected to an input/output (I/O) port 34 of a signal processor 36 which is inside of the device 10. The I/O device is also connected to the previously-mentioned antenna 38 through a receiver 40 and demodulator 42, as well as a modulator 44 and transmitter 46.

[0022] The signal processor 36 includes a central processing unit (CPU) 48 connected to a data, address and control bus 50 which is also connected to a random access memory (RAM) 52 and a computer-readable medium 54, which may be a read-only memory (ROM), miniature hard drive, or other device capable of saving encoded digital data.

[0023] The digital data stored in the computer-reada-

5

15

20

40

45

ble medium 54 may include a computer program such as shown in Fig. 4 for displaying three-dimensional icons according to the present invention, such as those shown in Figs. 2A-2F. Such a program can take the form shown in Fig. 4, but not necessarily. It can take other forms which would be equally valid for retrieving digital data representative of three-dimensional icons, according to the present invention. In any event, after entering in a step 56, a decision is made in a step 58 as to whether or not the signal processor 36 has received or has detected an event which would call for the display of a three-dimensional icon according to the present invention. Such an event might be an internal event within the signal processor or may be an external event, such as the depression of a button on the keypad or the reception of a signal over the antenna 38, or some other event or combination thereof. If not, the step is re-executed indefinitely. Such a program can be running in background in conjunction with other processes being executed in a multiprocessing environment or can be exited and returned to periodically. If such an event is detected, a step 60 is executed to retrieve digital data stored in the computer-readable medium 54 indicative of a threedimensional icon according to the present invention. The signal processor 36 then causes the retrieved digital data to be displayed on the display 14, as indicated by a step 62, e.g., by a graphics controller. A return is then made in a step 64 for further processing.

[0024] The computer-readable medium is encoded with a data structure for use in providing the three-dimensional graphical icon of the present invention. The data structure is encoded as digital data indicative of the graphical icon defined by alternating light and dark stripes. Selected stripes of the light and dark stripes change from light to dark. They may also change back to light again to indicate a shadow adjacent an edge of the icon. Stripes may also change from dark to light and stay that way or change back again to dark to indicate a highlight adjacent another edge of the icon. Altogether, the light and dark stripes with shadows and highlights provide the icon with a strong three-dimensional appearance.

[0025] The data structure stored in the computerreadable medium may be encoded according to a portable bitmap file format known in the art as "pbm". It is a lowest common denominator monochrome file format. Alternately, the structure can be encoded with other formats, such as "pgm" for portable graymap file format, or "ppm" for portable pixmap file format (lowest common denominator color image file format).

[0026] Although the invention has been shown and described with respect to a best mode embodiment thereof, it should be understood by those skilled in the art that the foregoing and various other changes, omissions and additions in the form and detail thereof may be made therein without departing from the spirit and scope of the invention.

### Claims

- 1. A computer-readable medium encoded with a data structure for use in providing a graphical icon for display on a display of a portable communications device, characterized in that said data structure is encoded as digital data indicative of said graphical icon defined by alternating light and dark stripes, that selected stripes of said light and dark stripes change from light to dark and back to light to indicate a shadow adjacent an edge of said icon and from dark to light and back to dark to indicate a highlight adjacent another edge of said icon, and that altogether said light and dark stripes with shadows and highlights provide said icon with a three-dimensional appearance.
- The computer-readable medium of claim 1, characterized in that said data structure is encoded according to a portable bitmap file format.
- The computer-readable medium of claim 1, characterized in that said data structure is encoded according to a portable graymap file format.
- The computer-readable medium of claim 1, characterized in that said data structure is encoded according to a portable color image file format.
- 30 5. A communication device, comprising:

means, responsive to an event in the communication device, for providing an event signal; a computer-readable medium encoded with a data structure for use in providing a graphical icon for display on a display of a portable communications device, wherein said data structure is encoded as digital data indicative of said graphical icon defined by alternating light and dark stripes, that selected stripes of said light and dark stripes change from light to dark and back to light to indicate a shadow adjacent an edge of said icon and from dark to light and back to dark to indicate a highlight adjacent another edge of said icon, and that altogether said light and dark stripes with shadows and highlights provide said icon with a three-dimensional appearance; and

means, responsive to the event signal, for retrieving the digital data from the computerreadable medium and causing said display of said graphical icon on said display according to said retrieved digital data.

- 5 6. The device of claim 5, wherein said data is encoded according to a portable bitmap file format.
  - 7. The computer-readable medium of claim 5, char-

acterized in that said data structure is encoded according to a portable graymap file format.

- 8. The computer-readable medium of claim 5, characterized in that said data structure is encoded according to a portable color image file format.
- 9. Method of displaying an icon on a portable communication device, comprising the steps of:

retrieving, in response to an event signal, digital data from a computer-readable medium, wherein said digital data is indicative of said icon defined by alternating light and dark stripes, that selected stripes of said light and dark stripes change from light to dark and back to light to indicate a shadow adjacent an edge of said icon and from dark to light and back to dark to indicate a highlight adjacent another edge of said icon, and that altogether said light and dark stripes with shadows and highlights provide said icon with a three-dimensional appearance; and displaying said icon in response to said digital data.

- The method of claim 9, wherein said digital data is encoded according to a portable bitmap file format.
- The method of claim 9, wherein said digital data is encoded according to a portable graymap file format.
- The method of claim 9, wherein said digital data is encoded according to a portable color image file format.

10

15

20


25


40


45

50


55







8



EP 1 209 651 A3 (11)

# **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3: 29.01.2003 Bulletin 2003/05 (51) Int Cl.7: G09G 3/20

(43) Date of publication A2: 29.05.2002 Bulletin 2002/22

(21) Application number: 01307922.3

(22) Date of filing: 18.09.2001

(84) Designated Contracting States: AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR **Designated Extension States:** AL LT LV MK RO SI

(30) Priority: 21.11.2000 US 717784


(71) Applicant: Nokia Corporation 02150 Espoo (FI)

(72) Inventor: Heiskari, Heli 20100 Turku (FI)

(74) Representative: Read, Matthew Charles et al Venner Shipley & Co. 20 Little Britain London EC1A 7DH (GB)

#### Three-dimensional icons for graphical user interface (54)

A strong three-dimensional icon is created for (57)low-resolution displays such as used in portable communication devices by alternating light and dark stripes, with some stripes changing from light to dark and back to light to indicate a shadow, and other stripes from dark to light and back to dark to indicate a highlight. Altogether, the light and dark stripes with shadows and highlights provide the icon with a strong three-dimensional appearance.





# **EUROPEAN SEARCH REPORT**

Application Number EP 01 30 7922

Category	Citation of document with in of relevant passa	dication, where appropriate, ges	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CI.7)	
	WO 00 57617 A (KRAF MOBILE PHONES LTD ( 28 September 2000 ( * abstract * * page 11, last par	FI)) 2000-09-28)	1-12	G09Ġ3/20	
				TECHNICAL FIELDS SEARCHED (Int.Cl.7)	
		. :		H04M G06F G06T G09G	
	·				
	The present search report has b	<u>-</u>	<u> </u>		
Place of search THE HAGUE		Date of completion of the search 3 December 2002	· ·		
X : parti Y : parti docu A : techi	THE TINGUE  ITEGORY OF CITED DOCUMENTS  cularly relevant if taken alone cularly relevant if combined with anoth ment of the same category nological background written disclosure	T: theory or princi E: earlier patent of after the filing of or D: document cite L: document cite	ple underlying the in locument, but publis late I in the application	ivention hed on, or	

EPO FORM 1503 03.82 (PO4C01)

## ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 01 30 7922

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-12-2002

Patent document cited in search report		ent iport	Publication date		Patent family member(s)		Publication date
WO 0	057617	A	28-09-2000	GB AU WO EP	2348082 A 3812500 A 0057617 A 1166533 A	<u> </u>	20-09-2000 09-10-2000 28-09-2000 02-01-2002
							•
					,		
			·				
				-			
					•		
			,				

 $\stackrel{Q}{\mathbb{D}}$  For more details about this annex : see Official Journal of the European Patent Office, No. 12/82